

The Hyper Photonix HSD1-400-DRP-C2S transceiver is designed for 2 km optical communication applications, and it is compliant with QSFP-DD MSA, CMIS 4.0, IEEE 802.3bs, and 400GAUI-8 standards. The 425 Gigabit signal is carried over four parallel lanes at 1310nm. The module's transmitter converts 8-channel 53.125 Gbps electrical data to 4 parallel optical output signals, each supporting 106.25 Gbps. The receiver converts 4-channel 106.25 Gbps optical input data to 8-channel electrical output data.

### Features

- QSFP-DD MSA 5.1 and CMIS 4.0 compliant
- MPO-12 APC connector
- 8x53.125Gbps PAM4 400GAUI-8 host interface
- 4x106.25Gbps (53.125GBd PAM4) optical signal
- Up to 2 km over SMF with KP-FEC
- Power dissipation ≤ 10W
- Operating case temperature: 0°C to 70°C
- IEEE 802.3bs 400GBASE-DR4 compliant
- Built-in digital diagnostic functions
- 3.3V power supply voltage
- RoHS compliant



### Applications

- 400GBASE-DR4 Ethernet
- Data center networks

### Specifications

Part Number	HSD1-400-DRP-C2S
Data Rate	425Gbps
Supply Voltage	3.3V
Power Consumption	≤ 10W
Wavelength	1310nm
Optical Connector	MPO-12
Transmitter	<b>Hyper Silicon™ Photonics</b>
Case Temperature	0°C to 70°C
Reach	2km over SMF